

Designed to be used with B070-008-19, B070-016-19, B072-008-1, B072-008-1A, [B072-016-1](#) or [B072-016-1A](#) NetCommander Cat5 KVM switches. Not for use with B070-008-19-IP, B070-016-19-IP, [B072-008-1-IP](#) or [B072-016-1-IP](#) NetCommander IP Cat5 KVM Switches

## KVM Switch Accessories - NetCommander USB Server Interface Unit (SIU)

MODEL NUMBER: **B078-101-USB**



### Description

The Tripp Lite NetCommander USB Server Interface Unit (SIU) connects to the HD15 port and USB port on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cables can then be used to connect the server to the switch ports on a Tripp Lite B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander Cat5 KVM switch. Use of Cat5e cables frees up space in the installation that would ordinarily be filled by traditional, thicker KVM cables.

### Features

- Needed to connect a USB Server to a B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100ft away from the KVM switch

### Highlights

- Needed to connect a USB Server to a B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply required
- Allows a recommended maximum distance of 100ft from KVM to computer/server via Cat5e cable
- Compact and lightweight design

### System Requirements

- Server or CPU with a HD15 port and a USB port
- A B070-008-19, B070-016-19, B072-008-1, B072-008-1A, B072-016-1 or B072-016-1A NetCommander Cat5 KVM Switch
- Not for use with B070-008-19-IP, B070-016-19-IP, B072-008-1-IP or B072-016-1-IP NetCommander IP Cat5 KVM Switches
- Cat5e/6 cable; up to 100ft

### Package Includes

- (x1) B078-101-USB USB Server Interface Unit (SIU)

## Specifications

### OVERVIEW



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

UPC Code	037332148421
Accessories Type	Server Interface Unit
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	3.600 x 1.600 x 0.900
Shipping Dimensions (hwd / cm)	9.14 x 4.06 x 2.29
Shipping Weight (lbs.)	0.4000
Shipping Weight (kg)	0.18
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>